HSA5

14 SEER SINGLE STAGE AIR CONDITIONER WITH OBSERVER® COMMUNICATING CONTROL SYSTEM

1½ THRU 5 TONS SPLIT SYSTEM
208 / 230 Volt, 1-phase, 60 Hz

TSTAT0201CW
Recommended
(sold separately)

REFRIGERATION CIRCUIT
- Copeland Scroll® compressors on select models
- Filter-drier supplied with every unit for field installation
- External high and low refrigerant service ports
- Copper tube/aluminum fin coil

PERFORMANCE
- Communicating, self-configuring operation when used with Observer® Wall Control (TSTAT0201CW)
- Outdoor temperature sensor factory installed
- Compressor sound blanket standard
- Isolation compressor grommets

EASY TO INSTALL AND SERVICE
- Text based Diagnostics with Observer communicating wall control
- Easy access service valves on all models
- Innovative control box design
- High and low pressure switches
- Fan motor in-line disconnect plug
- Only two screws to access control panel
- Factory charged with R-410A refrigerant

BUILT TO LAST
- High gloss, baked-on powder coat finish over galvanized steel
- Post-painted (black) coil fins
- Coated, weather-resistant cabinet screws
- Coated inlet grille with 3/8" (10mm) spacing for extra protection (hail guard)
- Corner posts for extra strength and style

WARRANTY*
- 3 year No Hassle Replacement™ limited warranty
- 5 year parts limited warranty (including compressor and coil)
  - With timely registration, an additional 5 year parts limited warranty (including compressor and coil)

* For residential applications only. See warranty certificate for complete details and restrictions, including warranty coverage for other applications.

AHRI CERTIFIED™ www.ahridirectory.org

Use of the AHRI Certified TM Mark indicates a manufacturer's participation in the program. For verification of certification for individual products, go to www.ahridirectory.org .

c UL us LISTED

UNIT PERFORMANCE DATA

Model Number	Size (tons)	Nominal Btu/hr	Min. Circuit Ampacity	Max. Fuse or Breaker	Operating Dimensions depth x width x height in. (mm)	Ship / Operating Weight lbs. (kg)	Notes
HSA518GKA	1½	18,000	11.8	20	31-3/16 x 31-3/16 x 28-11/16 (792.5 x 792.5 x 729.3)	213 / 176 (97 / 80)	
HSA524GKA	2	24,000	17.6	25	31-3/16 x 31-3/16 x 28-11/16 (792.5 x 792.5 x 729.3)	213 / 176 (97 / 80)	
HSA530GKA	2½	30,000	16.8	25	31-3/16 x 31-3/16 x 32-1/8 (792.5 x 792.5 x 815.6)	199 / 135 (90 / 75)	
HSA536GKA	3	36,000	18.1	30	31-3/16 x 31-3/16 x 35-1/2 (792.5 x 792.5 x 902)	211 / 177 (96 / 80)	
HSA542GKA	3½	42,000	22.3	35	31-3/16 x 31-3/16 x 28-11/16 (792.5 x 792.5 x 729.3)	237 / 203 (108 / 92)	
HSA548GKA	4	48,000	20.8	35	31-3/16 x 31-3/16 x 28-11/16 (792.5 x 792.5 x 729.3)	238 / 204 (108 / 93)	
HSA560GKA	5	60,000	27.5	40	31-3/16 x 31-3/16 x 32-1/8 (792.5 x 792.5 x 815.6)	257 / 225 (117 / 102)	